600W RGBAL 4-in-1 Beam, Wash, Spot & Profile Moving Head



Power. Precision. Performance.

The Torrent™ Keyframe 600 RGBAL is a professional 4-in-1 moving head with beam, wash, spot, and profile capabilities. Its 600W RGBAL 5-in-1 LED light source delivers exceptional brightness and accurate color with a CRI of 95 for natural skin tones on stage. A precision 180 mm lens ensures crisp projection, while dual rotating gobo wheels, framing shutters, and virtual CMY, CTO, and 66 color filters provide complete creative control.

Fully Equipped

Built for performance and versatility, this fixture combines high output with precise control. Dual rotating gobo wheels with replaceable gobos and a 4-blade framing shutter system with +/– 55° rotation provides exceptional creative flexibility. Its 5.9°–52° motorized zoom and smooth, accurate movements deliver reliable operation while DMX, RDM, Art-Net, and sACN connectivity ensure seamless integration in any production.

Luminous Intensity

Lux/M	10M	15M	20M	30M	50M
5.9°	12,500	5,556	3,125	1,389	500
52°	300	130	75	30	12

Main Features

- 600W RGBAL 5-in-1 LED (40,000 hrs)
- Color temperature: 2700K–8000K, CRI: Ra ≥ 95
- Zoom range: 5.9°–52°
- 66 color filters plus virtual CMY and CTO
- Dual rotating gobo wheels with replaceable gobos
- 4-blade framing shutters with +/– 55° rotation
- Octagonal prism with bidirectional rotation
- Dual frost effects (normal and heavy)
- 8/16-bit electronic focus for sharp projection
- 1–25 Hz strobe (random and pulse effects)
- Pan: 540°, Tilt: 270° (8/16-bit)
- Fixed lock: Y-axis lock
- Integrated dual clamp assembly
- Includes front-loading ATA spec flight case

Optical

600W RGBAL 5-in-1 LED, 40,000 hrs

Zoom range: 5.9°–52°

2700K–8000K

CRI: Ra ≥ 95

Weight & Dimensions

17.5 x 11.2 x 31 in (442 x 282 x 788 mm)

82.7 lbs. (37.5 kg)

Flight Case:

27.6 x 27.6 x 34.7 in (700 x 700 x 880 mm)

Qty. Per Case: 1

Control

USITT DMX-512, RDM, Art-Net, sACN

5-pin DMX in/out

60/35/64/49-channels

5-button control menu with LCD display

Power + Current

100-240VAC, 50-60 Hz

Consumption: 1,050W, 10.5A, PF: 0.996

PowerCON® TRUE1-compatible in/out

Warranty + Certifications

2-year limited warranty

CE, RoHS